



LM-193B LM-173B

SXGA LCD monitors in two sizes featuring an array of input/output terminals and functions for wide-ranging applications



■ High Contrast, High Resolution LCD Monitor

The LM-193B/173B LCD monitor offers a highly detailed image with its 1280 x 1024 pixel resolution, LED backlighting, 250 cd/m 2 brightness, and 1000:1 contrast ratio.

Also contributing to the monitor's excellent visibility are its ability to display 16.7 million colours, and a broad viewing angle of 85°/85° horizontally and 80°/80° vertically.

■ A Wide Range of Input and Output Terminals

The monitor is equipped with a wide range of terminals for connecting to various sources including BNC video in/out, S-Video in, mini-DIN 4pin x1, RGB In x1, and HDMI In x1. Built-in AC power with input power terminal on the back of the panel helps to make for clean cabling and easy handling of the monitor.

Lightweight and Slim Design

The monitor is lightweight in design as the 17-inch model weighs only 3.0 kg, or 3.6 kg for the 19-inch model, both with stand. To match the compact form, the monitor is framed with an attractive slim bezel. It also features built-in 0.5W x 0.5W speakers, making it a great replacement for existing CRT monitors in a variety of applications such as monitoring and control room usage.

Other features

- Multi-language on screen menu display: English, German, French, Spanish, Norwegian, Portuguese and Japanese
- Through output capability of video input / analogue audio input

LM-193B/LM-173B

Specifications

Model No.		LM-193B	LM-173B		
Display					
Display size/type		19" (48 cm)/LCD	17" (43 cm)/LCD		
Aspect ratio		5:4			
Dot pitch (per or	ne triad)	0.294 x 0.294 mm	0.264 x 0.264 mm		
Number of pixels		1280 (H) x 1024 (V)			
Brightness		250 cd/m ²			
Viewing angle		H: 170° (85°/ 85°), V: 160° (80°/ 80°) (typ.)			
Contrast ratio		1000 :1			
Display colour		16.7 million			
Response time		5 ms			
Terminal					
	Video	BNC (Input x 1, Output x 1)			
Video	S-Video	Input x 1, mini-DIN 4-pin			
VIGCO	RGB	Input x 1 , D-sub 15-pin x 1			
	HDMI	Input x 1 (type A)			
	Audio input	3.5 mm stereo jack x 1			
Audio	Audio output	3.5 mm stereo jack x 1			
Output power		0.5 W x2			
General					
Power source		AC 100 V - 240 V (50 Hz/60 Hz)			
Energy efficienc	y class	A			
Power	ON mode	15 W	13 W		
consumption	Stand-by mode	0.23W	0.23 W		
	Annual energy consumption	22 kWh/year *	19 kWh/year*		
External	without stand (W x H x D)	418.4 x 365.1 x 60.6 mm	371.9 x 317.3 x 60.3 mm		
dimensions	with stand (W x H x D)	418.4 x 412.2 x 180 mm	371.9 x 384.2 x 180 mm		
Weight (net) with/without stand		3.6 kg / 3.2 kg	3.0 kg / 2.6 kg		
Rated input current		0.59 A	0.51 A		
OSD languages		English, German, French, Italian, Spanish, Norwegian, Portuguese, Japanese			
VESA mount size		100 mm x 100 mm (M4 x 6 mm)			

^{*} Based on the power consumption of the television operating 4 hours per day or 365 days. The actual energy consumption will depend on how the television is used.

Available Signals

Signal name	Status	BNC/ S-VIDEO	VGA	номі
PAL	PAL	~	N	N
BW / 50	PAL	~	N	Ν
NTSC(3.58)	NTSC	~	N	N
BW / 60	NTSC	~	N	N
480 / 60i	720 x 480	N	N	~
480 / 59.94i	720 x 480	N	N	~
576 / 50i	720 x 576	N	N	~
480 / 60p	720 x 480	N	N	~
480 / 59.94p	720 x 480	N	N	~
576 / 50p	720 x 576	N	N	~
720 / 60p	1280 x 720	N	N	~
720 / 59.94p	1280 x 720	N	N	~
720 / 50p	1280 x 720	N	N	~
1080 / 60i	1920 x 1080	N	N	~
1080 / 59.94i	1920 x 1080	N	N	~
1080 / 50i	1920 x 1080	N	N	~
1080 / 60p	1920 x 1080	N	N	~

Signal name	Status	BNC/ S-VIDEO	VGA	номі
1080 / 59.94p	1920 x 1080	N	N	~
1080 / 50p	1920 x 1080	N	N	~
640 x 400 / 70Hz	640 x 400	N	~	~
640 x 480 / 60Hz	640 x 480	N	~	~
640 x 480 / 72Hz	640 x 480	N	~	~
640 x 480 / 75Hz	640 x 480	N	~	~
720 X 400 / 70Hz	720 x 400	N	~	~
800 x 600 / 56Hz	800 x 600	N	~	~
800 x 600 / 60Hz	800 x 600	N	~	~
800 x 600 / 72Hz	800 x 600	N	~	~
800 x 600 / 75Hz	800 x 600	N	~	~
1024 x 768 / 60Hz	1024 x 768	N	~	~
1024 x 768 / 70Hz	1024 x 768	N	~	~
1024 x 768 / 75Hz	1024 x 768	N	~	~
1280 x 1024 / 60Hz	1280 x 1024	N	~	~
1280 x 1024 / 75Hz	1280 x 1024	N	~	V

: AvailableNot available





AC Adaptor



Terminals

- 1 Audio output (3.5 mm stereo jack)
- 2 Audio input (3.5 mm stereo jack)
- 8 BNC output
- 4 BNC input
- 5 S-Video input (mini-DIN 4-pin)
- ⁶ VGA input (RGB; D-sub 15-pin)
- O HDMI input (type A)





HDMI, the HDMI logo and High-definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. All other brand or product names may be trademarks and/or registered trademarks of their respective owners. Any rights not expressly granted herein are reserved.

Copyright © 2016, JVCKENWOOD Corporation. All Rights Reserved.

Simulated pictures.
The values for weight and dimensions are approximate.
E.&O.E. Design and specifications subject to change without notice.



DISTRIBUTED BY